

# TRUTH SNAP<sup>®</sup> PLATE BACKER

LIGHTWEIGHT DESIGN / DURABLE MATERIAL



## NIJ STANDARD 0101.06 CERTIFIED

## LEVEL II

### PREMIUM 2.0 AAP201

Areal Density  
(ASTM D3776M-09A Option C)

0.79 lb/ft<sup>2</sup> • 3.86 kg/m<sup>2</sup>

Thickness (ASTM D1777)

0.16" • 0.41 cm

V-50 9mm FMJ

1722 fps • 525 m/s

V-50 .357 MAG

1679 fps • 515 m/s

Special Threats

Available Upon Request

PAIR WITH TRUTH SNAP ARMOR PLATES FOR STANDALONE USE

## NIJ STANDARD 0101.06 CERTIFIED

## LEVEL IIIA

	ELITE AAE3A01	ULTRA PREMIUM RISE, Ultra Premium, Male,	PREMIUM AAP3A03	STANDARD AAS3A01
Areal Density (ASTM D3776M-09A Option C)	0.88 lb/ft <sup>2</sup> • 4.30 kg/m <sup>2</sup>	0.97 lb/ft <sup>2</sup> • 4.74 kg/m <sup>2</sup>	1.13 lb/ft <sup>2</sup> • 5.51 kg/m <sup>2</sup>	1.24 lb/ft <sup>2</sup> • 6.05 kg/m <sup>2</sup>
Thickness (ASTM D1777)	0.25" • 0.64 cm	0.298" • 0.757 cm	0.238" • 0.604 cm	0.26" • 0.66 cm
V-50 .357 SIG	1868 fps • 569 mps	1888 fps • 575 m/s	1866 fps • 568 m/s	1785 fps • 544 m/s
V-50 .44 MAG	1717 fps • 523 mps	1730 fps • 527 m/s	1721 fps • 521 m/s	1583 fps • 483 m/s
Special Threats	Available Upon Request	<b>FBI Body Armor Test Protocol 4.1</b> • 9mm 124gr FMJ • .40 S&W 165gr GDHP • 9mm 127gr +P+ SXT • .45 AUTO	Available Upon Request	Available Upon Request

### AVAILABLE SIZES:

- 9 x 11" Shooter's Cut
- 9 x 11" Full Cut
- 10 x 12" Shooter's Cut
- 10 x 12" Full Cut



Durable, 200D  
nylon finish with  
weatherproof seal.

