

THE NEXT GENERATION IN OFFICER SAFETY

# TRUTH SNAP<sup>®</sup>

MODULAR  
PLATE  
SYSTEM



**308**  
ULTRA

**308**  
PREMIUM

**308**  
STANDARD

.308 + SPIKE LEVEL 3



**855**  
CERAMIC  
STRIKE FACE

**308**  
.308 / MSC / .556  
+ SPIKE LEVEL 3

**M855**  
COMBINED

NEVER GO TO YOUR TRUNK FOR ARMOR AGAIN™

## GROUNDBREAKING

- Thinnest, lightest, certified plate system on the market
- Patented, magnetic and modular SNAP system
- Proprietary, multi-curve design with a refined aesthetic finish

## SUPERIOR SAFETY

- Certified to NIJ 0101.06 Standard (Level III) — designed to be worn in conjunction with RISE Armor Packages or other soft body armor vests
- Advanced handgun, rifle, stab and special threat protection exceed NIJ standards
- Multi-round capable plates with dual-strike face design

## SCALABLE

- SNAP the 855 Strike Face Plate for tiered rifle and handgun protection — armor up or down
- Base Plate selections scale in weight, thickness and price
- Available in a variety of cuts and sizes



**308 STANDARD**  
AAS302

CERTIFIED TO NIJ STANDARD 0101.06 (LEVEL III) WHEN WORN IN CONJUNCTION WITH RISE LEVEL IIIA ULTRA PREMIUM ARMOR PACKAGE\*

CPL Model Designation: AAS302 ICW, RISE, Ultra, Premium, Male IIIA

SPECIAL THREAT PROTECTION

- Tested to NIJ 0101.07 standard when worn in conjunction with RISE Level II or Level IIIA Armor Packages:

7.62x51mm M80 Ball NATO FMJ Steel Jacket @ 2780 fps (847 m/s)

7.62x39mm MSC Type 56 @ 2400 fps (732 m/s)

5.56mm M193 @ 3250 fps (990 m/s)

ICW 855 Strike Face Plate: 5.56mm M855 @ 3115 fps (950 m/s)

- Meets NIJ 0115.00 Stab Resistance Spike Level III Standard

THICKNESS 0.70" (17.8mm)

AREAL DENSITY 3.46 lb/ft2 (1.69 g/cm2)

SIZES AND WEIGHTS

<b>5 x 8" Full Cut**</b> 0.96 lb (0.44 kg)
<b>7 x 9" Full Cut</b> 1.52 lb (0.69 kg)
<b>8 x 10" Shooter's Cut</b> 1.67 lb (0.76 kg)
<b>8 x 10" Full Cut</b> 1.94 lb (0.88 kg)
<b>9 x 11" Shooter's Cut</b> 2.10 lb (0.95 kg)
<b>9 x 11" Full Cut</b> 2.41 lb (1.09 kg)
<b>10 x 12" Shooter's Cut</b> 2.58 lb (1.17 kg)
<b>10 x 12" Full Cut</b> 2.94 lb (1.33 kg)



**308 PREMIUM**  
AAP301.1

CERTIFIED TO NIJ STANDARD 0101.06 (LEVEL III) WHEN WORN IN CONJUNCTION WITH RISE LEVEL IIIA STANDARD AND PREMIUM ARMOR PACKAGES\*

CPL Model Designation: AAP301.1 ICW AAS3A01  
CPL Model Designation: AAP301.1 ICW AAP3A03

SPECIAL THREAT PROTECTION

- Tested to NIJ 0101.07 standard when worn in conjunction with RISE Level II or Level IIIA Armor Packages:

7.62x51mm M80 Ball NATO FMJ Steel Jacket @ 2780 fps (847 m/s)

7.62x39mm MSC Type 56 @ 2400 fps (732 m/s)

5.56mm M193 @ 3250 fps (990 m/s)

ICW 855 Strike Face Plate: 5.56mm M855 @ 3115 fps (950 m/s)

- Meets NIJ 0115.00 Stab Resistance Spike Level III Standard

THICKNESS 0.62" (15.7mm)

AREAL DENSITY 3.02 lb/ft2 (1.47 g/cm2)

SIZES AND WEIGHTS

<b>6 x 6" Side Plate**</b> 0.76 lb (0.34 kg)
<b>5 x 8" Full Cut**</b> 0.84 lb (0.38 kg)
<b>7 x 9" Full Cut</b> 1.33 lb (0.60 kg)
<b>8 x 10" Shooter's Cut</b> 1.46 lb (0.66 kg)
<b>8 x 10" Full Cut</b> 1.70 lb (0.77 kg)
<b>9 x 11" Shooter's Cut</b> 1.83 lb (0.83 kg)
<b>9 x 11" Full Cut</b> 2.11 lb (0.96 kg)
<b>10 x 12" Shooter's Cut</b> 2.26 lb (1.03 kg)
<b>10 x 12" Full Cut</b> 2.57 lb (1.17 kg)

PENDING NIJ CERTIFICATION



**308 ULTRA**  
AAU301

CERTIFIED TO NIJ STANDARD 0101.06 (LEVEL III) WHEN WORN IN CONJUNCTION WITH RISE LEVEL IIIA ULTRA PREMIUM ARMOR PACKAGE\*

CPL Model Designation: AAU301 ICW RISE, Ultra Premium, Male, IIIA

SPECIAL THREAT PROTECTION

- Tested to NIJ 0101.07 standard when worn in conjunction with RISE Level II or Level IIIA Armor Packages:

7.62x51mm m80 ball nato fmj steel jacket @ 2780 fps (847 m/s)

7.62x39mm MSC Type 56 @ 2400 fps (732 m/s)

5.56mm M193 @ 3250 fps (990 m/s)

ICW 855 Strike Face Plate: 5.56mm M855 @ 3115 fps (950 m/s)

- Meets NIJ 0115.00 Stab Resistance Spike Level III Standard

THICKNESS 0.53" (13.5mm)

AREAL DENSITY 2.60 lb/ft2 (1.18 g/cm2)

SIZES AND WEIGHTS

<b>6 x 6" Side Plate**</b> 0.65 lb (0.29 kg)
<b>5 x 8" Full Cut**</b> 0.72 lb (0.33 kg)
<b>7 x 9" Full Cut</b> 1.14 lb (0.52 kg)
<b>8 x 10" Shooter's Cut</b> 1.26 lb (0.57 kg)
<b>8 x 10" Full Cut</b> 1.46 lb (0.66 kg)
<b>9 x 11" Shooter's Cut</b> 1.58 lb (0.72 kg)
<b>9 x 11" Full Cut</b> 1.81 lb (0.82 kg)
<b>10 x 12" Shooter's Cut</b> 1.94 lb (0.88 kg)
<b>10 x 12" Full Cut</b> 2.21 lb (1.00 kg)



**855**

SNAP THE 855 STRIKE FACE PLATE TO ANY TRUTH SNAP BASE PLATE FOR M855 PROTECTION.

TESTED TO NIJ STANDARD 0101.06 (LEVEL III) WHEN WORN IN CONJUNCTION WITH RISE ARMOR PACKAGES AND TRUTH SNAP BASE PLATES\*

- 7.62x51mm M80 Ball NATO FMJ Steel Jacket @ 2780 fps (847 m/s)

SPECIAL THREAT PROTECTION

- Tested to NIJ 0101.07 standard when worn in conjunction with RISE Armor Packages and Truth SNAP Base Plates:

5.56mm M855 @ 3115 fps (950 m/s)

THICKNESS 0.45" (11.43MM)

AREAL DENSITY 2.56 lb/ft2 (1.25 g/cm2)

SIZES AND WEIGHTS

<b>7 x 9" Full Cut</b> 1.39 lb (0.63 kg)
<b>8 x 10" Shooter's Cut</b> 1.53 lb (0.69 kg)
<b>8 x 10" Full Cut</b> 1.77 lb (0.80 kg)
<b>9 x 11" Shooter's Cut</b> 1.89 lb (0.86 kg)
<b>9 x 11" Full Cut</b> 2.18 lb (0.99 kg)
<b>10 x 12" Shooter's Cut</b> 2.35 lb (1.07 kg)
<b>10 x 12" Full Cut</b> 2.69 lb (1.22 kg)

855 STRIKE FACE PLATE MUST BE WORN WITH ICW TRUTH SNAP BASE PLATES.

**308 STANDARD + 855**

THICKNESS 1.15" (29.23MM)

AREAL DENSITY 6.02 lb/ft2 (2.94 g/cm2)

SIZES AND WEIGHTS

<b>7 x 9" Full Cut</b>	2.91 lb (1.32 kg)
<b>8 x 10" Shooter's Cut</b>	3.20 lb (1.45 kg)
<b>8 x 10" Full Cut</b>	3.71 lb (1.68 kg)
<b>9 x 11" Shooter's Cut</b>	3.99 lb (1.81 kg)
<b>9 x 11" Full Cut</b>	4.59 lb (2.08 kg)
<b>10 x 12" Shooter's Cut</b>	4.93 lb (2.24 kg)
<b>10 x 12" Full Cut</b>	5.63 lb (2.55 kg)



**308 PREMIUM + 855**

THICKNESS 1.07" (27.13MM)

AREAL DENSITY 5.58 lb/ft2 (2.72 g/cm2)

SIZES AND WEIGHTS

<b>7 x 9" Full Cut</b>	2.72 lb (1.23 kg)
<b>8 x 10" Shooter's Cut</b>	2.99 lb (1.36 kg)
<b>8 x 10" Full Cut</b>	3.47 lb (1.57 kg)
<b>9 x 11" Shooter's Cut</b>	3.72 lb (1.68 kg)
<b>9 x 11" Full Cut</b>	4.29 lb (1.95 kg)
<b>10 x 12" Shooter's Cut</b>	4.61 lb (2.09 kg)
<b>10 x 12" Full Cut</b>	5.26 lb (2.39 kg)



PENDING NIJ CERTIFICATION

**308 ULTRA + 855**

THICKNESS 0.98" (24.93MM)

AREAL DENSITY 5.16 lb/ft2 (2.43 g/cm2)

SIZES AND WEIGHTS

<b>7 x 9" Full Cut</b>	2.53 lb (1.15 kg)
<b>8 x 10" Shooter's Cut</b>	2.79 lb (1.27 kg)
<b>8 x 10" Full Cut</b>	3.23 lb (1.47 kg)
<b>9 x 11" Shooter's Cut</b>	3.47 lb (1.57 kg)
<b>9 x 11" Full Cut</b>	3.99 lb (1.80 kg)
<b>10 x 12" Shooter's Cut</b>	4.29 lb (1.95 kg)
<b>10 x 12" Full Cut</b>	4.90 lb (2.22 kg)



\*Independently tested in accordance with NIJ standards. Full test details and reports available upon request.



# TRUTH SNAP<sup>®</sup> PLATE BACKER

LIGHTWEIGHT DESIGN / DURABLE MATERIAL



## NIJ STANDARD 0101.06 CERTIFIED

## LEVEL II

Areal Density  
(ASTM D3776M-09A Option C)

Thickness (ASTM D1777)

V-50 9mm FMJ

V-50 .357 MAG

Special Threats

### PREMIUM 2.0 AAP201

0.79 lb/ft<sup>2</sup> • 3.86 kg/m<sup>2</sup>

0.16" • 0.41 cm

1722 fps • 525 m/s

1679 fps • 515 m/s

Available Upon Request

PAIR WITH TRUTH SNAP ARMOR PLATES FOR STANDALONE USE

## NIJ STANDARD 0101.06 CERTIFIED

## LEVEL IIIA

Areal Density  
(ASTM D3776M-09A Option C)

Thickness  
(ASTM D1777)

V-50 .357 SIG

V-50 .44 MAG

Special Threats

### ELITE AAE3A01

0.88 lb/ft<sup>2</sup> • 4.30 kg/m<sup>2</sup>

0.25" • 0.64 cm

1868 fps • 569 mps

1717 fps • 523 mps

Available Upon Request

### ULTRA PREMIUM RISE, Ultra Premium, Male,

0.97 lb/ft<sup>2</sup> • 4.74 kg/m<sup>2</sup>

0.298" • 0.757 cm

1888 fps • 575 m/s

1730 fps • 527 m/s

#### FBI Body Armor Test Protocol 4.1

- 9mm 124gr FMJ
- .40 S&W 165gr GDHP
- 9mm 127gr +P+ SXT
- .45 AUTO

### PREMIUM AAP3A03

1.13 lb/ft<sup>2</sup> • 5.51 kg/m<sup>2</sup>

0.238" • 0.604 cm

1866 fps • 568 m/s

1721 fps • 521 m/s

Available Upon Request

### STANDARD AAS3A01

1.24 lb/ft<sup>2</sup> • 6.05 kg/m<sup>2</sup>

0.26" • 0.66 cm

1785 fps • 544 m/s

1583 fps • 483 m/s

Available Upon Request

#### AVAILABLE SIZES:

- 9 x 11" Shooter's Cut
- 9 x 11" Full Cut
- 10 x 12" Shooter's Cut
- 10 x 12" Full Cut



PAIR WITH  
TRUTH SNAP  
PLATE SYSTEM

Durable, 200D  
nylon finish with  
weatherproof seal.



PROTECTION AT A HIGHER LEVEL<sup>®</sup>